



LUMENS / <i>Lumens</i>	fino a / up to 8340
EFFICIENZA / <i>efficiency</i>	128lm/W@700mA
COLLEGAMENTO/ <i>Wiring</i>	ECG / DALI a richiesta
TEMPERATURA COLORE / <i>CCT</i>	3000-4000 K
INDICE RESA CROMATICA / <i>CRI</i>	> 80
STRUTTURA / <i>Housing</i>	Alluminio / Aluminium
SCHERMO / <i>Diffuser</i>	Polycarbonato opale/ <i>opal Polycarbonate</i>
TESTATE / <i>end caps</i>	ABS
DISTRIBUZIONE / <i>light distribution</i>	Diretta / Direct
FINITURA / <i>Finish</i>	Bianco RAL 9003/ <i>White Ral 9003</i>



drawing #1



lumen	CCT	potenza	Dimensioni (A)	Peso
(lm)	(K)	(W)	(mm)	(kg)
2470	3000	20	612	2,01
2600	4000	20	612	2,01
3160	3000	27	612	2,01
3330	4000	27	612	2,01
4655	3000	36	1172	2,54
4900	4000	36	1172	2,54
6175	3000	52	1172	2,54
6500	4000	52	1172	2,54
5600	3000	45	1452	3,65
5900	4000	45	1452	3,65
7920	3000	67	1452	3,65
8340	4000	67	1452	3,65

LED	ECG		IP 54	IK 06	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	--	-------	-------	--------------------	--	----------------------	--	--	--

Schede tecniche complete varianti disponibili su www.mgilluminazone.it