


LUMENS/ <i>Lumens</i>	fino a /upto 16300
EFFICIENZA/ <i>efficiency</i>	139lm/W@700mA
COLLEGAMENTO/ <i>Wiring</i>	ECG / DALI arichiesta
TEMPERATURA COLORE/ <i>CCT</i>	da 3000K a 5000K
INDICE RESA CROMATICA/ <i>CRI</i>	80/90
STRUTTURA/ <i>Housing</i>	AL EN AB46100 pressofusione / <i>diecast</i>
SCHERMO/ <i>Diffuser</i>	Vetro extrachiaro 4mm/ <i>Extra clear glass4mm</i>
LENTI/ <i>Lences</i>	PMMA
DISTRIBUZIONE // <i>lightdistribution</i>	Asimmetrica/Simmetrica 60°, 90°,120°
FINITURA/ <i>Finish</i>	NERO/ <i>Black</i>
VERNICIATURA/ <i>Paint</i>	Polvere poliestere resistente UV/ <i>UV resistant polyesterpowder</i>



lumen	CCT	potenza	Dimensioni	Peso
(lm)	(K)	(W)	(mm)	(kg)
8880	4000	40	255x315x129	4,00
11680	4000	80	255x315x129	4,00
16300	4000	120	255x315x129	4,00

LED	ECG	IP 66	IK 08	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	-------	-------	--------------------	---	----------------------	---	---	---

Schede tecniche complete varianti disponibili su [www.mgilluminazione.it](http://www.mgilluminazione.it)