


LUMENS / <i>Lumens</i>	fino a / up to 5730
EFFICIENZA / <i>efficiency</i>	125lm/W@700mA
COLLEGAMENTO/ <i>Wiring</i>	ECG
TEMPERATURA COLORE / <i>CCT</i>	3000-4000 K
INDICE RESA CROMATICA / <i>CRI</i>	> 80
STRUTTURA / <i>Housing</i>	Profilo Alluminio Anodizzato / <i>Anodised Aluminium profile</i>
SCHERMO / <i>Diffuser</i>	PMMA opale/ <i>opal PMMA</i>
TESTATE / <i>end caps</i>	Alluminio Anodizzato / <i>Anodised aluminium</i>
DISTRIBUZIONE / <i>light distribution</i>	Diretta / <i>Direct</i>
FINITURA / <i>Finish</i>	Bianco RAL 9003/ <i>White Ral 9003</i>



lumen	potenza	Dimensioni (A)	Peso
(lm)	(W)	(mm)	(kg)
2470	20	612	2,01
2600	20	612	2,01
3160	27	612	2,01
3330	27	612	2,01
4655	36	1172	2,54
4900	36	1172	2,54
6175	52	1172	2,54
6500	52	1172	2,54

LED	ECG		IP 21	IK	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	--	-------	----	--------------------	--	----------------------	--	--	--

Schede tecniche complete varianti disponibili su [www.mgilluminaazione.it](http://www.mgilluminaazione.it)