




LUMENS / <i>Lumens</i>	fino a / up to	2540
EFFICIENZA / <i>efficiency</i>	102 lm/w - 94 lm/w	
COLLEGAMENTO / <i>Wiring</i>	ECG	
TEMPERATURA COLORE / <i>CCT</i>	3000/4000/5000 K	
INDICE RESA CROMATICA / <i>CRI</i>	>80	
STRUTTURA / <i>Housing</i>	Nylon rinforzato / <i>reinforced nylon</i>	
SCHERMO / <i>Diffuser</i>	Polycarbonato opale autoest. / <i>opal polycarbonate self exting</i>	
LENTI / <i>Lences</i>		
DISTRIBUZIONE / <i>light distribution</i>	diretta 160° / <i>direct 160°</i>	
COLORI / <i>Colours</i>	Bianco, Nero, Grigio / <i>White, Black, Grey</i>	
VERNICIATURA / <i>Paint</i>		



lumen	CCT	potenza	Dimensioni	Peso
(lm)	(K)	(W)	(mm)	(kg)
1790	4000 K	16w	95x290	1-1,2
2540	4000 K	25w	110x375	1-1,2

LED	ECG		IP 65	IK 09	GARANZIA 5 ANNI		240V 50-60 HZ		MADE IN ITALY
-----	-----	--	-------	-------	--------------------	--	------------------	--	---------------

Schede tecniche complete varianti disponibili su www.mgilluminazone.it