


LUMENS / <i>Lumens</i>	fino a / up to 9600
EFFICIENZA / <i>efficiency</i>	118lm/W@700mA
COLLEGAMENTO/ <i>Wiring</i>	ECG / DALI a richiesta
TEMPERATURA COLORE / <i>CCT</i>	4000 K
INDICE RESA CROMATICA / <i>CRI</i>	80-89
STRUTTURA / <i>Housing</i>	
SCHERMO / <i>Diffuser</i>	
UGR	
DISTRIBUZIONE / <i>light distribution</i>	Simmetrica/Symmetric
FINITURA / <i>Finish</i>	Bianco RAL 9003/ <i>White Ral 9003</i>



lumen	CCT	potenza	Dimensioni	Peso
(lm)	(K)	(W)	(mm)	(kg)
2125	4000	18	1165x62x78	2,1
4250	4000	36	1165x62x78	2,1
3540	4000	30	1460x62x78	2,6
6500	4000	55	1460x62x78	2,6
4800	4000	41	1722x62x78	3,1
9600	4000	82	1722x62x78	3,1

DISPONIBILE A RICHIESTA / AVAILABLE ON REQUEST

SENSORE / SENSOR

EMERGENZA INTEGRALE 3H / INTEGRAL EMERGENCY 3H

+ SELF TEST

LED	ECG		IP 20	IK	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	--	-------	----	--------------------	--	----------------------	--	--	--

Schede tecniche complete varianti disponibili su [www.mgilluminazone.it](http://www.mgilluminazone.it)