

LUMENS / <i>Lumens</i>	fino a / up to	2550
EFFICIENZA / <i>efficiency</i>	85lm/W@700mA	
COLLEGAMENTO/ <i>Wiring</i>	ECG /	
TEMPERATURA COLORE / <i>CCT</i>	4200 K	
INDICE RESA CROMATICA / <i>CRI</i>	80	
STRUTTURA / <i>Housing</i>	Base pressofusione alluminio/ <i>Die cast Aluminium base</i>	
SCHERMO / <i>Diffuser</i>	copertura PVC/ <i>PVC cover</i>	
LENTI / <i>Lences</i>	PMMA	
DISTRIBUZIONE / <i>light distribution</i>		
FINITURA / <i>Finish</i>	NERO/ <i>Black</i>	
VERNICIATURA / <i>Paint</i>	Polvere poliestere resistente UV/ <i>UV resistant polyester powder</i>	

lumen	CCT	potenza	Dimensioni	modello
(lm)	(K)	(W)	(mm)	
2550	4200	30	264x309x182	standard
2550	4200	30	264x309x182	photocell
2550	4200	30	264x309x182	emergenza
2550	4200	30	264x309x182	Emergenza phot.

LED	ECG		IP 65	IK	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	--	-------	----	--------------------	---	----------------------	---	---	--

Schede tecniche complete varianti disponibili su www.mgilluminaazione.it