


LUMENS/ <i>Lumens</i>	fino a / upto	312000
EFFICIENZA/ <i>efficiency</i>	140lm/W@700mA	
COLLEGAMENTO/ <i>Wiring</i>	ECG / DALI arichiesta	
TEMPERATURA COLORE/ <i>CCT</i>	4000K	
INDICE RESA CROMATICA/ <i>CRI</i>	70/79	
STRUTTURA/ <i>Housing</i>	Alluminio / <i>Alluminium</i>	
SCHERMO/ <i>Diffuser</i>	Vetro extrachiaro 4mm/ <i>Extra clear glass4mm</i>	
LENTI/ <i>Lences</i>	Rifratore/ <i>refractor</i>	
DISTRIBUZIONE / <i>lightdistribution</i>	Simmetrico/ <i>Symmetric 15°/30°/60°</i>	
FINITURA/ <i>Finish</i>	Grigio / <i>Grey</i>	
VERNICIATURA/ <i>Paint</i>	Polvere poliestere resistente UV/ <i>UV resistant polyester powder</i>	



lumen (lm)	CCT (K)	potenza (W)	Dimensioni (mm)	Peso (kg)
56800	4000	400	480x545x338	20,00
69500	4000	500	480x545x338	20,00
81600	4000	600	480x545x338	20,00
111200	4000	800	891x549x338	36,00
136000	4000	1000	891x549x338	36,00
159600	4000	1200	891x549x338	36,00
217600	4000	1600	977x522x600	54,00
266000	4000	2000	977x522x600	54,00
312000	4000	2400	977x522x600	54,00

LED	ECG	IP 66	IK 10	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	-------	-------	--------------------	--	----------------------	--	--	--

Schede tecniche complete varianti disponibili su www.mgilluminazione.it