


LUMENS / <i>Lumens</i>	fino a / up to 16300
EFFICIENZA / <i>efficiency</i>	139lm/W@700mA
COLLEGAMENTO / <i>Wiring</i>	ECG / DALI a richiesta
TEMPERATURA COLORE / CCT	4000 K
INDICE RESA CROMATICA / CRI	> 80
STRUTTURA / <i>Housing</i>	AL EN AB46100 pressofusione / die cast
SCHERMO / <i>Diffuser</i>	Vetro extrachiaro 4mm/Extra clear glass 4mm
LENTI / <i>Lences</i>	PMMA
DISTRIBUZIONE / <i>light distribution</i>	Asimmetrica/Simmetrica 60°, 90°, 120°
FINITURA / <i>Finish</i>	NERO/Black
VERNICIATURA / <i>Paint</i>	Polvere poliestere resistente UV/UV resistant polyester powder



lumen	CCT	potenza	Dimensioni	Peso
(lm)	(K)	(W)	(mm)	(kg)
8880	4000	40	255x315x129	4,00
11680	4000	80	255x315x129	4,00
16300	4000	120	255x315x129	4,00

LED	ECG	ECG DALI On request	IP 65	IK	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	---------------------------	-------	----	--------------------	--	----------------------	--	--	--

Schede tecniche complete varianti disponibili su www.mgilluminazone.it